

# DP 全锥大通道



## 设计特点






1. 具有最大自由通道的全锥形喷嘴
2. 两个特殊的S型内部叶片
3. 公接头或母接头
4. 法兰连接可用

## 喷雾性能

1. 喷雾模式：全锥形
2. 喷雾角度：30°，60°，90° and 120°
3. 流量：2.65-3701.73 l/m.

## 应用

1. 船用废气洗涤器
2. 海洋工业冷却用废气洗涤器



# DP 全锥大通道

## 性能参数

### dp流量和尺寸

全锥，超窄30 (NN)，窄60 (n)，介质90 (m) 和宽120 (W) 喷雾角，3/8~4管尺寸

外螺纹 内螺纹 管尺寸	喷嘴数	每分钟加仑										大约自由 通道直径 (in)	近似尺寸 平均长度 最大				金属 重量 (磅)		
		3 PSI	5 PSI	7 PSI	10 PSI	15 PSI	20 PSI	30 PSI	40 PSI	60 PSI	80 PSI		30° A	60° A	90° A	120° A B			
3/8	125	0.70	0.89	1.04	1.23	1.49	1.70	2.06	2.35	2.85	3.26	0.125	-	1.50	1.50	1.50	0.88	0.19	
	156	1.11	1.41	1.65	1.95	2.36	2.70	3.27	3.74	4.52	5.18								0.156
	187	1.60	2.03	2.38	2.82	3.41	3.90	4.72	5.40	6.54	7.48								0.188
1/2	187	1.60	2.03	2.38	2.82	3.41	3.90	4.72	5.40	6.54	7.48	0.188	-	1.88	1.88	1.88	1.00	0.28	
	218	2.54	3.32	3.79	4.48	5.42	6.20	7.50	8.59	10.4	11.9								0.219
	250	2.87	3.65	4.27	5.05	6.11	7.00	8.47	9.70	11.7	13.4								0.250
3/4	281	3.53	4.48	5.25	6.21	7.51	8.60	10.4	11.9	14.4	16.5	0.281	4.00	2.50	2.50	1.25	0.50		
	312	4.26	5.42	6.35	7.51	9.08	10.4	12.6	14.4	17.4	20.0							0.290	
	343	5.21	6.62	7.75	9.17	11.1	12.7	15.4	17.6	21.3	24.4							0.344	
	375	6.15	7.82	9.16	10.8	13.1	15.0	18.1	20.8	25.1	28.8							0.375	
1	375	6.15	7.82	9.16	10.8	13.1	15.0	18.1	20.8	25.1	28.8	0.375	4.38	2.94	2.94	1.50	0.78		
	406	7.38	9.38	11.0	13.0	15.7	18.0	21.8	24.9	30.2	34.5							0.406	
	437	8.61	10.9	12.8	15.2	18.3	21.0	25.4	29.1	35.2	40.3							0.438	
1 1/4	437	8.61	10.9	12.8	15.2	18.3	21.0	25.4	29.1	35.2	40.3	0.438	5.38	3.38	3.38	2.00	1.34		
	500	11.1	14.1	16.5	19.5	23.6	27.0	32.7	37.4	45.2	51.8							0.500	
	531	12.3	15.6	18.3	21.7	26.2	30.0	36.3	41.6	50.3	57.6							0.531	
	562	13.5	17.2	20.1	23.8	28.8	33.0	39.9	45.7	55.3	63.3							0.562	
1 1/2	562	13.5	17.2	20.1	23.8	28.8	33.0	39.9	45.7	55.3	63.3	0.550	7.25	4.38	4.38	2.25	2.00		
	593	15.4	19.5	22.9	27.1	32.8	37.5	45.4	51.9	62.8	71.9							0.594	
	625	16.4	20.8	24.4	28.9	34.9	40.0	48.4	55.4	67.0	76.7							0.625	
	656	19.9	25.3	29.6	35.0	42.4	48.5	58.7	67.2	81.3	93.0							0.656	
2	687	20.9	26.6	31.1	36.8	44.6	51.0	61.7	70.6	85.5	97.8	0.688	8.25	7.19	6.30	6.30	2.69	3.50	
	750	25.4	32.3	37.9	44.8	54.2	62.0	75.0	85.9	104	119								0.750
	812	27.9	35.4	41.5	49.1	59.4	68.0	82.3	94.2	114	130								0.813
	875	34.4	43.8	51.3	60.6	73.4	84.0	102	116	141	161								0.875
	937	38.5	49.0	57.4	67.9	82.1	94.0	114	130	158	180								0.938
	1000	45.1	57.3	67.2	79.4	96.1	110	133	152	184	211								1.00
2 1/2	1125	55.3	70.4	82.4	97.5	118	135	163	187	226	259	1.12	10.3	7.63	6.00	6.75	3.25	3.75	
	1250	66.4	84.4	98.9	117	142	162	196	224	271	311								1.24
	1375	79.5	101	118	140	169	194	235	269	325	372								1.37
	1500	97.6	124	145	172	208	238	288	330	399	457								1.50
	1500	97.6	124	145	172	208	238	288	330	399	457								1.46
	1625	115	146	171	202	245	280	339	388	469	537								1.62
3	1750	131	167	195	231	280	320	387	443	536	614	1.75	13.5	11.0	9.00	9.88	4.75	7.25	
	1750	131	167	195	231	280	320	387	443	536	614								1.75
	1875	148	188	220	260	314	360	436	499	603	691								1.87
4	2000	173	220	258	305	369	422	511	585	707	810	1.96	16.0	10.7	8.88	9.81	4.78	8.00	
	2125	193	245	287	339	411	470	569	651	788	902								2.12
	2250	209	266	311	368	446	510	617	706	855	978								2.25
	2250	209	266	311	368	446	510	617	706	855	978								2.25